

Oily Water Separators

detegasa



**The best combination
of reliability, simplicity
and economy**



EDIT
AUTOMATION



Oily Water Separators

The ideal blend of reliability, simplicity, and cost-effectiveness. in an oil separation system. Detegasa Oily Water Separators have been designed to separate hydrocarbons from the water located in the bilge of the ship, discharging an effluent with oil content below 15 ppm, in compliance with IMO regulations. This becomes mandatory for 400 GT vessels and bigger.

- **Capacities of treatment from 0,5 to 10 m³ per hour**
- **IMO MEPC 107(49) MED Type approved**
- **Customizable to fulfil special requirements (ATEX, Navy, ...)**
- **Two-stage function: first stage (gravity) and second stage (emulsions adsorption)**
- **Wide range for crew on board from 10 to 400 people**
- **5 ppm's feature available**



detegasa

- **Bilge monitor designed by Detegasa**
- **Smooth operation on board**
- **Reliable performance**
- **Easy installation**
- **Low maintenance**
- **New model (OWSAN-P) with control panel that integrates oil monitor and HMI**



EDIT

AUTOMATION

We edit. You lead.

15-17 Akti Kountouriotou, 185 34,
Piraeus, Attica, Greece

+30 210 4110 007
info@edit.com.gr
www.edit.com.gr